

BIBO Installation Instructions



Please note these instructions should be used in conjunction with the BIBO user's manual and the BIBO self-installation kit both of which should have been delivered with your BIBO. The user's manual can also be viewed online at www.bibowater.co.uk/customer-service

These instructions should be followed by a plumber, kitchen fitter, builder, water cooler installer or similarly-experienced person. If at all unsure please call us on 0800 678 5969 and ask to speak to one of our engineers.

Water Supply Connection

In case you need to turn off the mains water supply to your home, identify where the tap/isolation valve is located.

Preparation

1. As well as your BIBO the box contains a self-installation kit consisting of a length of water pipe, a BIBO 'T' connector, a shut-off valve & a right angle fitting. (There is included an additional length of pipe with a straight connector if needed). The metal fitting in the drip tray is not needed & can be discarded.
2. When you've decided where to locate your BIBO identify a suitable mains cold water supply nearby. More often than not this will be under your kitchen sink or behind your dishwasher or washing machine. Ideally this should be a 15mm, copper pipe in good condition with enough of the pipe exposed to enable you insert the BIBO 'T' connector.
3. Often there is a valve to enable you to isolate the chosen pipe. If not then it will be necessary to turn off the main water supply to your home. Be sure to drain as much water as possible from the pipe before cutting it.
4. Using a suitable pipe cutter make two cuts in the pipe removing a 20mm section.
5. Push the two exposed ends of the copper pipe firmly into each end of the BIBO 'T' connector.
6. Make sure the tap on the BIBO 'T' connector is turned off i.e. parallel to the copper pipe.
7. Turn the water supply back on and make sure there are no leaks where the copper pipe fits into the BIBO 'T' connector.
8. Push the 6mm (white) water supply pipe provided with your BIBO firmly into the fitting on the 'T' piece.
9. Run this pipe behind or underneath your kitchen base cabinets then bring it up through the worktop behind your BIBO.
10. Push the end of the pipe into the (blue & white) shut-off valve (supplied with the BIBO 'T' connector).

Installation

Safety tips:

- Remember your BIBO weighs 15.5kgs so take care when lifting it from its box.
- Install your BIBO in a cool, dry place where it is well ventilated. It must be kept away from any heat source.
- Keep the rear of your BIBO at least 10cm (4") away from the wall.
- The water pressure should be between 1bar (14psi) & 6bar (87psi)
- Your BIBO needs a normal 13amp power supply.

1. Carefully remove the packaging & place your BIBO in its preferred location on the work surface.
2. Remove the plastic bag & protective covering from the cable & plug.
3. Remove the drip tray wrapping & the UV lamp 'key' (keep this in a safe place) from inside the drip tray.
4. Remove the protective cover from the touch screen.
5. Remove the locking clip & blanking plug from the inlet water fitting on the back of your BIBO (see the pictures on page 17 of the user's manual for guidance).
6. Push the right angle water fitting (supplied with the BIBO 'T' connector) into the water inlet then replace the locking clip.
7. Push the short length of pipe from the shut-off valve into the right angle fitting.

Setting Up

Safety tip: Make sure both power switches on the back of your BIBO are in the off position before connecting to the power supply (see the illustration on page 4 of the user's manual for guidance).

Now follow the instructions on Using Your BIBO on pages 6-12 of the user's manual & follow the BIBO's on-screen prompts. **PLEASE ENSURE THAT YOU DO NOT TURN THE BIBO'S HOT TANK SWITCH ON (THIS IS ON BACK OF UNIT, CLEARLY LABELLED) UNTIL BIBO HAS FILLED ITSELF WITH WATER.** If you have any questions please call us: 0800 678 5969.

We hope you enjoy your new BIBO!

www.bibowater.co.uk 0800 678 5969